

**Positively
Emulsifies Oily
Soil—Saves Time
and Labor**

**Contains No
Solvents or
Caustic—Safer
to Use**

**Works on Any
Oily Soil—
Simplifies
Training**

**Contains
Corrosion
Inhibitors—Use
in Autoscrubbers
and Prevents
Flash Rusting**

Equipment List

- ✓ Single disc floor machine or autoscrubber
- ✓ Wet vacuum
- ✓ Grit-type brushes for autoscrubber
- ✓ Deck brush
- ✓ Looped-end cotton mop
- ✓ Mop bucket with wringer
- ✓ Dust mop
- ✓ Scraper

Available in size:
½ gallon containers.

Wear safety equipment recommended on MSDS, place wet floor signs and read all directions and cautions prior to beginning work.



DEGREASER

POSITIVE EMULSION DEGREASER/CLEANER

Professional Recommendations

- Use this product regularly for best results
- **NOT** recommended for removal of baked-on or dried, hardened soils
- Use "grit" type brushes on autoscrubber to enhance cleaning on unfinished concrete and other industrial floors.
- Overlap cleaning passes to assure uniform cleaning and "double scrub" when heavy soil is present
- When mop cleaning, change cleaning solution frequently to get peak performance.
- **DO NOT** let mop rest in cleaning solution between uses

Surface Safety


- Safe on most surfaces found in industrial settings
- Before cleaning aluminum, brass, copper or other non-ferrous metals, check for safety. If metal bubbles or darkens when concentrate is applied, **DO NOT** use this product on that surface
- **NOT** recommended on glass

Specifications

Appearance	Red liquid
Odor	None
Density (lbs/gal)(±0.1 @20°C)	.8.69
pH (conc.)(±0.5 @20°C)	12.6
Refractive index (± .0020 @20°C)	1.3506
Hard water tolerance (as ppm CaCO ₃)	Greater than 8000 ppm
Flashpoint	None
USDA rating	A-1
Foam generation	Moderate
Stability (40°-120°F)	Stable
Freeze/thaw stability	OK, 3 cycles
Shelf life (closed containers, 40°-120°F)	1 year minimum



Remove loose soil and garbage. Before cleaning floors, place Wet Floor signs near work area.



Apply to surface liberally while scrubbing. Allow to work. If soil is heavy, double scrub with an auto scrubber (First pass, squeegee up; second pass, squeegee down, vac on). Pick up as much solution as possible. If possible, allow floor to dry before traffic resumes on cleaned area.