

MATERIAL SAFETY DATA SHEET

DATE PREPARED: 3/1/2007

(Prepared According to 29 CFR 1910.1200)

CODE: 9256

SECTION 1 - PRODUCT IDENTIFICATION				
Distributor Custom Solutions		Emergency Phone 800-309-5869		
Address 900 E. 103rd Street, Chicago, IL 60628		Prepared By: LPL		
Trade Name BRILLIANCE		Product Type Stainless Steel Polish		
SECTION 2 - INGREDIENTS				
CHEMICAL NAME/COMMON NAME	CAS NO.	WT. %(opt)	TLV(Source)	TITLE III, SECT. 313
Mineral Spirits	64741-65-7	25 - 30	100ppm(TWA)	NO
Isoparaffinic Solvent	64741-66-8	40 - 50%	400 ppm (TWA)	NO
1-Methyl-2Pyrrolidinone	872-50-4	<5%	100ppm (TWA)	YES
Mineral Oil	8042-47-5	15 - 20%	5mg/m3 (TWA as mist)	NO
Liquefied Petroleum Gas	68476-85-7	10%	1000ppm (TWA/PEL)	NO
SECTION 3 - PHYSICAL DATA				
Boiling point (°F.) NA	Specific Gravity (H2O=1.0) <1.0 ± 0.005	pH NA		
Vapor Pressure (mm Hg) 60psig @130F	Vapor Density (Air=1) >1			
Solubility in water	<input type="checkbox"/> Complete	<input type="checkbox"/> Insoluble	<input type="checkbox"/> Emulsifiable (or Dispersible)	<input checked="" type="checkbox"/> Slight (or Partial)
Evaporation Rate (vs. H2O) <input checked="" type="checkbox"/> Faster	<input type="checkbox"/> Slower	<input type="checkbox"/> About the Same	Appearance and Odor Clear with hydrocarbon odor.	
SECTION 4 - FIRE AND EXPLOSION HAZARD DATA				
Flash Point (T.C.C.) <100F (Flammable) °F.	<input type="checkbox"/> None to Boiling	Flammable Limits	Upper 9.2	Lower 1.8
Extinguishing Media Carbon dioxide, foam and/or dry chemical may be used.				
Special Firefighting Procedures Containers should be cooled with water to prevent vapor pressure build up.				
Unusual Fire and Explosion Hazards At elevated temperatures (over 54C-130F) containers may vent or burst.				
SECTION 5 - REACTIVITY DATA				
Stability Stable	Incompatibility Oxidizing agents			
Hazardous Decomposition Products Oxides of carbon.				
SECTION 6 - HEALTH HAZARD DATA				
Primary Routes of Exposure	<input checked="" type="checkbox"/> Eye	<input checked="" type="checkbox"/> Skin	<input checked="" type="checkbox"/> Oral	<input checked="" type="checkbox"/> Inhalation
Signs and Symptoms Of Overexposure (Acute) High vapor concentrations may result in central nervous system depression and evidenced by giddiness, headache and nausea. Ingestion may result in vomiting. Prolonged or repeated skin contact can result in drying and defatting of skin. Moderate eye irritant.				
Signs and Symptoms of Overexposure (Chronic) None currently known.				
Medical Conditions Aggravated by Overexposure Pre-existing skin or eye disorders may be aggravated by exposure to this product.				
Carcinogen or Suspect Carcinogen Ingredients <input type="checkbox"/> NTP <input type="checkbox"/> IARC <input type="checkbox"/> OSHA <input checked="" type="checkbox"/> NONE				
SECTION 7 - EMERGENCY AND FIRST AID PROCEDURES				
Eyes	Flush eyes with water for at least 15 minutes and call a physician immediately.			
Skin	Wash affected areas with large amounts of soap and water. If irritation persists call physician.			
Ingestion	Do not induce vomiting. Contact local poison control center or physician immediately.			
Inhalation	Remove to fresh air. Start artificial respiration if necessary. Oxygen may be administered. Call a physician.			
SECTION 8 - SPECIAL PROTECTION INFORMATION				
Respiratory Protection Not required under normal use conditions with good general ventilation. Protect against generated mists/sprayback.				
Ventilation Requirements	<input type="checkbox"/> Local Exhaust	<input checked="" type="checkbox"/> Mechanical	<input type="checkbox"/> Other	Eye Protection Safety Glasses/Goggles
Protective Gloves Rubber/PVC	Other Protective Clothing Protective clothing appropriate to minimize contact during specific operations.			
SECTION 9 - SPILL OR LEAK PROCEDURES				
Steps To Be Taken If Released or	Remove all sources of ignition and ventilate area. Soak up spill with an inert absorbent and place into a designated disposal container.			
Waste Disposal Methods	When contents depleted, depress button until all gas is expelled. Dispose of container according to Federal, State and local regulations.			
SECTION 10 - STORAGE AND HANDLING INFORMATION				
Precautions to be Taken In Handling and Storage	Avoid breathing vapor. Keep away from heat and flame. Use with adequate ventilation. Do not expose to direct sunlight or store at temperatures above 130F (54C). Do not puncture or incinerate containers. Store as Level 3 Aerosol (NFPA 30B)			

The health hazards given on this Material Safety Data Sheet apply to this product in its concentrated form (as supplied) and may differ significantly at use dilution. The signs and symptoms of overexposure apply only to negligence in handling or misuse of the concentrated product and not to the routine exposure of the diluted product under conditions of ordinary use.

**HMIS
HAZARD
RATING**

HEALTH	2
FLAMMABILITY	4
REACTIVITY	0
PERSONAL PROTECTION	B

0 - LEAST
1 - SLIGHT
2 - MODERATE
3 - HIGH
4 - EXTREME