



# CUSTOM SOLUTIONS

## Anti-Slip Gloss Restorer

**Cleans,  
Restores,  
Makes  
Floors Safer**

# GLOSS KEEPER

## ANTI-SLIP GLOSS RESTORER

### Professional Recommendations

- Use diluted ratio only
- Gloss Keeper is to be used only as a restorer over existing finish
- Burnish only when thoroughly dry to avoid swirl marks, improper curing and dulling
- For best results use only clean mops and equipment
- When cleaning, flip pad to remove all surface soil

### Specifications


Appearance	Clear liquid
Odor	Pleasant, spring like
pH (concentrate)	9.0
Specific gravity	1.030
Flashpoint (TCC)	None
Slip resistance (ASTM #D2047-82)	Exceeds Underwriters Laboratories requirements for slip resistance
Coverage	.40,000 sq.ft./qt.

### Equipment List


- ✓ Wet floor signs
- ✓ Mop bucket with liner
- ✓ Looped-end rayon mop
- ✓ Burnisher and high speed burnishing pad
- ✓ Autoscrubber with red pad
- ✓ Clean spray bottle

Available in sizes:  
1, 2.5 and 55 gallon containers.


Wear safety equipment recommended on MSDS, place wet floor signs and read all directions and cautions prior to beginning work.




Remove gross soils (labels, gum). Dust mop floor. Divide floor into workable sections. Place wet floor caution signs near work area.




Dilute from 1/2 ounce to 6 ounces per gallon of water, according to preferred method of application.



For spray application, apply diluted solution in coarse stream ahead of burnisher. Burnish to high gloss.



For mop application, apply diluted solution and allow to work for 3 to 5 minutes. Pick up solution. Allow floor to dry, then burnish to a high gloss.



For autoscrubber application, scrub with red pad and use double scrub procedure. Pick up solution with second pass. Allow floor to dry. burnish to a high gloss.

