



CUSTOM SOLUTIONS

Fast Action Stripper

**No Scrub,
No Rinse
Nonbutyl
Formula**

**Slow
Evaporation**

High Productivity

Equipment List

- ✓ Wet floor signs
- ✓ Single disk floor machine or autoscrubber
- ✓ Wet vacuum
- ✓ Black, brown or high productivity pads
- ✓ Looped-end cotton mop
- ✓ Mop bucket with wringer
- ✓ Dust mop
- ✓ Edge tool
- ✓ Scraper
- ✓ Walk-off towel
- ✓ Squeegee

Available in sizes:
1, 2.5 and 55 gallon containers.

Wear safety equipment recommended on MSDS, place wet floor signs and read all directions and cautions prior to beginning work.



STRONG SAFETY


FAST ACTION STRIPPER

Professional Recommendations


- Schedule floor stripping based upon traffic wear and desired appearance
Do not buff a bare dry floor before coating — asbestos could be released into the air
- **Do not** strip linoleum or rubber tiles with Strong Safety — It will remove binding oils and embrittle the floor
- Use Strong Safety at recommended dilutions only. Stripping solution will dry too quickly and possibly reharden causing removal problems
- **Always** damp mop up residual stripping solution — “Rinse Free” means no flood rinse is required

Specifications

Appearance	Clear liquid
Odor	Citrus
Density (lb/gal)	8.76
pH (concentrate/1%)	13.5/11.0
Hard water tolerance (hardness as CaCO ₃)	Approx.3300 ppm
Stability (40°-120°F)	OK in closed containers
Freeze/thaw stability	OK, 3 cycles with thawing and agitation
D.O.T. hazard class/ID No.	Corrosive liquid/UN3267
Flashpoint (TCC)	Greater than 200°F




Remove gross soils (labels, gum). Dust mop floor. Divide floor into workable section. Place wet floor caution sign near work areas.



Dilute Strong Safety 4:1 (32 oz. per gallon) or as needed, with warm water. Apply to surface liberally using mop or autoscrubber.



Allow 5-10 minutes for stripper to work. Do not allow solution to dry.



Use a stripping pad on autoscrubber or single disk floor machine. Scrub thoroughly to remove all old coatings.



Check edges and baseboards for build-up. Remove with doodlebug or pad center. Scrub and pick up with automatic or wet vac.



Damp mop lightly with cool clean water to remove all residue. Allow floor to dry before sealing.