



# CUSTOM SOLUTIONS

Positively Emulsifies Oily Soil—Saves Time and Labor

Contains No Solvents or Caustic—Safer to Use

Works on Any Oily Soil—Simplifies Training

Low Foaming, Contains Corrosion Inhibitors—Use in Autoscrubbers and Prevents Flash Rusting

### Equipment List

- ✓ Single disc floor machine or autoscrubber
- ✓ Wet vacuum
- ✓ Grit-type brushes for autoscrubber
- ✓ Deck brush
- ✓ Looped-end cotton mop
- ✓ Mop bucket with wringer
- ✓ Dust mop
- ✓ Scraper

Available in sizes:  
1 and 55 gallon containers.

Wear safety equipment recommended on MSDS, place wet floor signs and read all directions and cautions prior to beginning work.



# FOODSERVICE DEGREASER

## EMULSIFIES GREASY SOILS

### Professional Recommendations

- Use this product regularly for best results
- **NOT** recommended for removal of baked-on or dried, hardened soils
- Use "grit" type brushes on autoscrubber to enhance cleaning on unfinished concrete and other industrial floors.
- Overlap cleaning passes to assure uniform cleaning and "double scrub" when heavy soil is present
- When mop cleaning, change cleaning solution frequently to get peak performance.
- **DO NOT** let mop rest in cleaning solution between uses

### Surface Safety


- Safe on most surfaces found in industrial settings
- Before cleaning aluminum, brass, copper or other non-ferrous metals, check for safety. If metal bubbles or darkens when concentrate is applied, **DO NOT** use this product on that surface
- **NOT** recommended on glass

### Specifications


Appearance	Clear, pink liquid
Density (lbs/gal)(±0.1 @20°C)	.8.7
pH (Conc./1%)(±0.5 @20°C)	12.3/10.4
Refractive index (±0.0020 @20°C)	1.3466
Hard water tolerance (hardness as ppm CaCO <sub>3</sub> )	Greater than 3500 ppm
Total alkalinity (% CaCO <sub>3</sub> )	.2.8
Foam generation	Moderate
USDA rating	A-1
Stability (40°-120°F)	Stable
Freeze/thaw stability	OK 3 cycles
Shelf life (Closed containers, 40°-120°F)	.1 year minimum



Wear safety equipment recommended on MSDS. Read all directions and cautions prior to beginning work. Remove loose soil and garbage. Before cleaning floors, place Wet Floor signs near work area.



Dilute **Degreaser** with water as follows:  
Heavy Soil: 5:1 (26 oz. per gallon)  
Moderate Soil: 20:1 (6 oz. per gallon)  
Light Soil: 50:1 (2.5 oz. per gallon)



Apply to surface liberally while scrubbing. Allow to work. If soil is heavy, double scrub with an auto scrubber (First pass, squeegee up; second pass, squeegee down, vac on). Pick up as much solution as possible. If possible, allow floor to dry before traffic resumes on cleaned area.