

SYNERGY

FUSION SC

**CLEANER DEGREASER WITH D-MARK
FOR RUBBER MARK REMOVAL**

**Recognized by
the USEPA
Design for the
Environment**

**Cleans and
Degreases at Mild
pH Levels**

**Removes Stubborn
Rubber Burn
Marks**

**Contains
No Section 313
Chemicals**

**Apply Using Any
Mechanical
Cleaning Device**

**Superconcentrated
for Most
Economical Use**

Equipment List

- ✓ Wet floor signs
- ✓ Autoscrubber with grit type brushes
- ✓ Wet vacuum
- ✓ Looped-end cotton mop
- ✓ Mop bucket with wringer
- ✓ Pressure washer
- ✓ Push broom

Available in sizes:
2.5 and 55 gallon containers.

Wear safety equipment recommended on MSDS, place wet floor signs and read all directions and cautions prior to beginning work.



Professional Recommendations


- Use this product regularly for best results
- Rinse out autoscrubber lines after each use of this product to protect hoses
- Use "grit" type brushes on your autoscrubber to enhance cleaning on unfinished concrete and other industrial floors
- Overlap your cleaning passes to assure uniform cleaning and "double scrub" when heavy soil is present
- When mop cleaning, change cleaning solution frequently to get peak cleaning performance
- **Do not** let mop rest in cleaning solution between uses

Specifications


Appearance	Clear, blue liquid
Odor	Mild, characteristic
Density (lbs/gal)(±0.1 @20°C)	8.71
pH (Conc.)(±0.2 @20°C)	10.6
Refractive index (±0.0020 @20°C)	1.3745
Foam generation	Low-moderate
Stability (40°-120°F)	Stable
Freeze/thaw stability	OK 3 cycles
Shelf life (Closed containers, 40°-120°F)	1 year minimum
D.O.T. classification	Not regulated
Biodegradable (per 16CFR260)	Yes
Section 313 chemicals	None
Volatile organic compounds (VOC)-%	None



Wear safety equipment recommended on MSDS. Read all directions and cautions prior to beginning work. Remove loose soil and garbage. Before cleaning floors, place Wet Floor signs near work area.



Dispense **Fusion SC** into cleaning equipment using our Connex-Safe® dispensing system.



Apply to surface liberally while scrubbing. Allow to work. If soil is heavy, double scrub with an auto scrubber (First pass, squeegee up; second pass, squeegee down, vac on). Pick up as much solution as possible. If possible, allow floor to dry before traffic resumes on cleaned area.



Recognized for Safer Chemistry
www.epa.gov/dfe

ACTIBLEND
SYSTEMS

CUSTOM SOLUTIONS Chicago, Illinois 800.621.8553 Fax 773.247.2036 www.customsol.com

MD398
8716
08/09