



CUSTOM SOLUTIONS

Recognized by the USEPA Design for the Environment

Instantly Removes Oily Soils

Removes Rubber Marks Easily

Contains Only Readily Biodegradable Ingredients

Concentrated for Maximum Economy Use

Equipment List

- ✓ Wet floor signs
- ✓ Autoscrubber with grit type brushes
- ✓ Wet vacuum
- ✓ Looped-end cotton mop
- ✓ Mop bucket with wringer
- ✓ Push broom

Available in sizes:
2.5, 55 gallon containers and
55 gallon Connex-Safe® for
dispensing systems.

Wear safety equipment recommended on MSDS, place wet floor signs and read all directions and cautions prior to beginning work.



FUSION DG

MULTI-PURPOSE DEGREASER WITH D-MARK FOR OUTSTANDING RUBBER MARK REMOVAL

Professional Recommendations

- Use this product regularly for best results
- **USE** "grit" type brushes on your autoscrubber to enhance cleaning on unfinished concrete and other industrial floors
- Overlap your cleaning passes to assure uniform cleaning and "double scrub" when heavy soil is present
- When mop cleaning, change cleaning solution frequently to get peak performance. Do not let mop rest in cleaning solution between uses

Surface Safety


- Safe on most industrial surfaces

Specifications

Appearance	Clear, yellow liquid
Odor	Mild, characteristic
Density (lbs/gal)(±0.1 @20°C)	8.72
pH (Conc. ±0.2 @20°C)	10.6
Refractive index (±0.0020 @20°C)	1.3629
Foam generation	Moderate
Stability (40°-120°F)	Stable
Freeze/thaw stability	OK 3 cycles
Shelf life (Closed containers, 40°-120°F)	1 year minimum
D.O.T. classification	Not regulated
Biodegradable (per 16CFR260)	Yes
Section 313 chemicals	None
Volatile organic compounds (VOC)-%	None



Wear safety equipment recommended on MSDS. Read all directions and cautions prior to beginning work. Remove loose soil and garbage. Before cleaning floors, place Wet Floor signs near work area.



Dilute **Fusion DG** with water as follows:
General Cleaning: 1:32 to 1:128
Floor with Tire Marks: 1:15
Heavy Tire Marks and Soils: 1:4 to 1:8
Note: Using warm water when diluting **Fusion DG** will help to remove rubber tire marks more easily.



Apply to surface liberally while scrubbing. Allow to work. If soil is heavy, double scrub with an auto scrubber (First pass, squeegee up; second pass, squeegee down, vac on). Pick up as much solution as possible. If possible, allow floor to dry before traffic resumes on cleaned area.



Recognized for Safer Chemistry
www.epa.gov/dfc