

# SYNERGY

# FORTIFIED DEGREASER

**Solvent Fortified  
Formula for  
Complete Cleaning**

**Patented Formula  
Instantly  
Emulsifies Oily  
Soils**

**Produces Fast,  
Economical  
Cleaning**

**Contains Corrosion  
Inhibitors—Safe  
on Most Industrial  
Surfaces and  
Equipment**

## Equipment List

- ✓ Wet floor signs
- ✓ Autoscrubber with grit type brushes
- ✓ Wet vacuum
- ✓ Looped-end cotton mop
- ✓ Mop bucket with wringer
- ✓ Push broom

Available in sizes:  
2.5 and 55 gallon containers.

Wear safety equipment recommended on MSDS, place wet floor signs and read all directions and cautions prior to beginning work.



## Professional Recommendations

- This is an excellent "catch-up" cleaner that will perform best when used regularly
- **USE** "grit" type brushes on your autoscrubber to enhance cleaning on unfinished concrete and other industrial floors
- Overlap your cleaning passes to assure uniform cleaning and "double scrub" when heavy soil is present
- When mop cleaning, change cleaning solution frequently to get peak performance. Do not let mop rest in cleaning solution between uses

## Surface Safety


- Safe on most industrial surfaces
- **NOT** recommended for use on brass, copper or aluminum

## Specifications

Appearance	Clear, purple liquid
Odor	Solvent
Density (lbs/gal)(±0.1 @20°C)	7.92
pH (Conc. ±0.5 @20°C)	8.0
Refractive index (±0.0020 @20°C)	1.4295
Solvent %	60.0
Flashpoint (°F)	153
Foam generation	Moderate
Stability (40°-120°F)	Stable
Freeze/thaw stability	OK 3 cycles
Shelf life (Closed containers, 40°-120°F)	1 year minimum



Wear safety equipment recommended on MSDS. Read all directions and cautions prior to beginning work. Remove loose soil and garbage. Before cleaning floors, place Wet Floor signs near work area.



Dispense Fortified Degreaser into cleaning equipment.



Apply to surface liberally while scrubbing. Allow to work. If soil is heavy, double scrub with an auto scrubber (First pass, squeegee up; second pass, squeegee down, vac on). Pick up as much solution as possible. If possible, allow floor to dry before traffic resumes on cleaned area.

**ACTIBLEND**  
SYSTEMS